

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CERAMIZER Detox Diesel System Pro D1753

Revision: 15.10.2025

Product code: 100931

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

CERAMIZER Detox Diesel System Pro D1753

UFI: 9DH0-09VQ-M007-HQFF

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Other vehicle (all types) cleaning and care products
cleaning agent for fuel systems
cleaning agent for diesel engines

1.3. Details of the supplier of the safety data sheet

Company name: Ceramizer D. Kosiorek Spółka Komandytowa
Street: Bartycka 116
Place: PL-00-716 Warsaw
Telephone: +48 22 498 09 08
E-mail: info@ceramizer.pl
Contact person: Customer Service
E-mail (Contact person): info@ceramizer.pl
Internet: www.ceramizer.com
Responsible Department: Customer Service

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Flam. Liq. 3; H226
Acute Tox. 4; H332
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H335
STOT RE 2; H373
Asp. Tox. 1; H304
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics
xylene
2-ethylhexanol
ethylbenzene

Signal word:

Danger

Pictograms:**Hazard statements**

H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CERAMIZER Detox Diesel System Pro D1753

Revision: 15.10.2025

Product code: 100931

Page 2 of 12

Hazard statements

H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331	Do NOT induce vomiting.
P405	Store locked up.
P501	Dispose of this material and its container to hazardous or special waste collection point. Dispose of waste according to applicable legislation.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics			60 - < 80 %
	918-481-9		01-2119457273-39	
	Asp. Tox. 1; H304 EUH066			
1330-20-7	xylene			10 - < 20 %
	215-535-7	601-022-00-9	01-2119488216-32	
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3, STOT RE 2, Asp. Tox. 1; H226 H332 H312 H315 H319 H335 H373 H304			
104-76-7	2-ethylhexanol			10 - < 20 %
	203-234-3		01-2119487289-20	
	Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2, STOT SE 3; H332 H315 H319 H335			
100-41-4	ethylbenzene			1 - < 10 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
64742-94-5	Hydrocarbons, C10, aromatics, <1% naphthalene			1 - < 10 %
	918-811-1		01-2119463583-34	
	STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H336 H304 H411			
160901-19-9	Alcohols, C12-13- branched and linear, ethoxylated			1 - < 10 %
	931-954-4			
	Acute Tox. 4, Eye Dam. 1, Aquatic Chronic 3; H302 H318 H412			

Full text of H and EUH statements: see section 16.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

CERAMIZER Detox Diesel System Pro D1753

Revision: 15.10.2025

Product code: 100931

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-48-9	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	60 - < 80 %
		inhalation: LC50 = >5 mg/l (dusts or mists); dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
1330-20-7	215-535-7	xylene	10 - < 20 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	
104-76-7	203-234-3	2-ethylhexanol	10 - < 20 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = >3000 mg/kg; oral: LD50 = 2047 mg/kg	
100-41-4	202-849-4	ethylbenzene	1 - < 10 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists)	
64742-94-5	918-811-1	Hydrocarbons, C10, aromatics, <1% naphthalene	1 - < 10 %
		inhalation: LC50 = 4688 mg/l (vapours); dermal: LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
160901-19-9	931-954-4	Alcohols, C12-13- branched and linear, ethoxylated	1 - < 10 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >300-2000 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. Medical treatment necessary.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂), Foam, Extinguishing powder. alcohol resistant foam, Sand,

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CERAMIZER Detox Diesel System Pro D1753

Revision: 15.10.2025

Product code: 100931

Page 4 of 12

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with:
Pyrophoric or self-heating substances.
Oxidising agent

7.3. Specific end use(s)

cleaning agent for diesel engines

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
104-76-7	2-Ethylhexan-1-ol	1	5.4		TWA (8 h)	
100-41-4	Ethylbenzene	100	442		TWA (8 h)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CERAMIZER Detox Diesel System Pro D1753

Revision: 15.10.2025

Product code: 100931

Page 5 of 12

Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
		200	884		STEL (15 min)	
1330-20-7	Xylene, mixed isomers, pure	50	221		TWA (8 h)	
		100	442		STEL (15 min)	

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	light yellow
Odour:	characteristic

Test method

Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	136-210 °C	
Flammability:	not determined	
Lower explosion limits:	0,6 vol. %	
Upper explosion limits:	8 vol. %	
Flash point:	46 °C	ISO 3679
Auto-ignition temperature:	not determined	
Decomposition temperature:	not determined	
pH-Value:	not applicable	
Viscosity / kinematic (at 40 °C):	1,3 mm ² /s	DIN EN ISO 3104
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents	not determined	
Partition coefficient n-octanol/water:	not determined	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CERAMIZER Detox Diesel System Pro D1753

Revision: 15.10.2025

Product code: 100931

Page 6 of 12

Vapour pressure (at 50 °C):	0,2 hPa	DIN EN ISO 13016-1
Density (at 20 °C):	0,82 g/cm ³	DIN 12185
Relative density:	not determined	
Relative vapour density:	not determined	

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

The product is not: Explosive.

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) 4,412 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics				
	oral	LD50 >5000 mg/kg	Rat	OECD 401	
	dermal	LD50 >5000 mg/kg	Rabbit	OECD 402	
	inhalation (4 h) dust/mist	LC50 >5 mg/l	Rat	OECD 403	
1330-20-7	xylene				
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

CERAMIZER Detox Diesel System Pro D1753

Revision: 15.10.2025

Product code: 100931

Page 7 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
104-76-7	2-ethylhexanol				
	oral	LD50 2047 mg/kg	Rat	OECD 401	
	dermal	LD50 >3000 mg/kg	Rat	OECD 402	
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
100-41-4	ethylbenzene				
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
64742-94-5	Hydrocarbons, C10, aromatics, <1% naphthalene				
	oral	LD50 >5000 mg/kg	Rat		OECD 401
	dermal	LD50 >2000 mg/kg	Rabbit		OECD 402
	inhalation vapour	LC50 4688 mg/l	Rat		OECD 403
160901-19-9	Alcohols, C12-13- branched and linear, ethoxylated				
	oral	LD50 >300-2000 mg/kg	Rat		
	dermal	LD50 >2000 mg/kg	Rabbit		

Irritation and corrosivity

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/eye irritation: Causes serious eye irritation.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure. (xylene)

Aspiration hazard

May be fatal if swallowed and enters airways.

Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. Special hazards arising from the substance or mixture!

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic life with long lasting effects.

CERAMIZER Detox Diesel System Pro D1753

Revision: 15.10.2025

Product code: 100931

Page 8 of 12

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h][d]	Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics					
	Acute fish toxicity	LC50 1000 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 1000 mg/l	72 h	Pseudokirchneriella subcapitata		
	Acute crustacea toxicity	EC50 1000 mg/l	48 h	Daphnia magna (Big water flea)		
104-76-7	2-ethylhexanol					
	Acute fish toxicity	LC50 17,1 mg/l	96 h	Leuciscus idus (golden orfe)		
	Acute algae toxicity	ErC50 11,5 mg/l	72 h	Scenedesmus quadricauda		
	Acute crustacea toxicity	EC50 39 mg/l	48 h	Daphnia magna (Big water flea)		
64742-94-5	Hydrocarbons, C10, aromatics, <1% naphthalene					
	Acute fish toxicity	LC50 >=2-<=5 mg/l	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute crustacea toxicity	EC50 >=3-<=10 mg/l	48 h	Daphnia magna (Big water flea)		
160901-19-9	Alcohols, C12-13- branched and linear, ethoxylated					
	Acute fish toxicity	LC50 >1-10 mg/l	96 h	Poecilia reticulata (Guppy)	OECD 203	
	Acute crustacea toxicity	EC50 >1-10 mg/l	48 h	Daphnia magna (Big water flea)	OECD 202	

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics			
		80%	28	
104-76-7	2-ethylhexanol			
	OECD 301C/ ISO 9408/ EEC 92/69/V, C.4-F	>80%	14	

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	4,2-7,2

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CERAMIZER Detox Diesel System Pro D1753

Revision: 15.10.2025

Product code: 100931

Page 9 of 12

organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - used product

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number: UN 1307
14.2. UN proper shipping name: XYLENES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1307
14.2. UN proper shipping name: XYLENES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Limited quantity: 5 L

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CERAMIZER Detox Diesel System Pro D1753

Revision: 15.10.2025

Product code: 100931

Page 10 of 12

Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number or ID number: UN 1307
14.2. UN proper shipping name: XYLENES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: 223
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1307
14.2. UN proper shipping name: XYLENES
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: A3
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Information according to Directive 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CERAMIZER Detox Diesel System Pro D1753

Revision: 15.10.2025

Product code: 100931

Page 11 of 12

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 12,14.

Abbreviations and acronyms

Flam. Liq. 2: Flammable liquids, hazard category 2
Flam. Liq. 3: Flammable liquids, hazard category 3
Acute Tox. 4: Acute toxicity, hazard category 4
Asp. Tox. 1: Aspiration hazard, hazard category 1
Skin Irrit. 2: Skin irritation, hazard category 2
Eye Dam. 1: Serious eye damage, hazard category 1
Eye Irrit. 2: Eye irritation, hazard category 2
STOT SE 3: Specific target organ toxicity - single exposure, hazard category 3
STOT RE 2: Specific target organ toxicity - repeated exposure, hazard category 2
Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard category: Chronic 2
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard category: Chronic 3
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation
intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see table at <http://abbrev.esdscom.eu>

Safety Data Sheet

according to Regulation (EC) No 1907/2006

CERAMIZER Detox Diesel System Pro D1753

Revision: 15.10.2025

Product code: 100931

Page 12 of 12

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Acute Tox. 4; H332	Calculation method
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H335	Calculation method
STOT RE 2; H373	Calculation method
Asp. Tox. 1; H304	Calculation method
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)